

OPTIKA B-510BF represents the ideal, ultra-modern, advanced routine microscope for efficient analysis in transmitted light applications, equipped with the state-of-the-art, exclusive X-LED³ illumination system, designed by OPTIKA. Carefully engineered considering all the relevant aspects for users, this series offers user-friendly operations, robustness, durability and superb resolution, delivering contrasted and sharp images through the impressive optics and the Köhler diaphragm.

Rubber cups, retractable protections Exclusive, state-of-the-art illumination system for a higher comfort **B-510BF** Plan wide field eyepieces PL 10x with F.N. of 22 mm, X-LED3 high eyepoint (3.6 W) as transmitted light Trinocular port for a Achieve unmatched colour fidelity camera, with 50/50 light distribution and brightness with daylight white colour temperature (6,300 K) and cut electricity bills by 90%, saving money and energy. 30° inclined Siedentopf tube, +/- 5 dioptric compensation, on left eyepiece Carrying handle High contrast and resolution IOS W-PLAN (4x, 10x, 40x, 100x) Sturdy, stable and wide-dimensioned body Rackless mechanical stage (233 x 147 mm) Coaxial coarse and fine focusing mechanism with double Vernier scale, (graduated, 0.002 mm) anti-scratch surface Swing-out condenser, Right-handed, X/Y controls sliding-in, with 0.2/0.9 in ergonomic position N.A. and centering system Full Köhler illumination system High-efficiency **X-LED**³ as transmitted light for brightfield observation



B-510BF - Technical Datasheet

Observation Methods	Brightfield
Head	Trinocular, 30° inclined, splitting ratio eyepieces/photo tube: 50% - 50%
Eyepieces	Plan wide field, PL 10x/22, high eyepoint, with dioptric adjustment on left eyepiece
Nosepiece	Quintuple, reversed
Objectives	IOS W-PLAN 4x, 10x, 40x, 100x (oil)
Stage	Rackless, mechanical, 233x147 mm, 78x54 mm movement range
Focusing	Coaxial coarse & fine (200µm/turn), upper stop, adjustable tension
Transmitted Illumination & Diaphragms	High-efficiency X-LED³ (3.6 W), manual brightness control. Köhler illumination system with field diaphragm
Condenser	N.A. 0.2/0.9, swing-out, sliding-in and with centering system

Accessories		Included ■ Optional
M-1001	PL10x/22 eyepieces (pair), high eyepoint, with rubber cup (retractable)	
M-1003	PL15x/16 eyepieces (pair), high eyepoint	
M-781	PL10x/22 eyepiece, high eyepoint, with micrometric scale (10mm/100um) & rubber cup (retractable)	
M-1049	IOS W-PLAN objective 2x/0.08	
M-1125	IOS W-PLAN objective 4x/0.10	
M-1126	IOS W-PLAN objective 10x/0.25	
M-1127	IOS W-PLAN objective 20x/0.40	
M-1128	IOS W-PLAN objective 40x/0.65	
M-1129	IOS W-PLAN objective 60x/0.80	
M-1130	IOS W-PLAN objective 100x/1.25 (oil)	
M-1131	IOS W-PLAN POL objective 4x/0.10	
M-1132	IOS W-PLAN POL objective 10x/0.25	
M-1133	IOS W-PLAN POL objective 20x/0.45	
M-1134	IOS W-PLAN POL objective 40x/0.65	
M-1135	IOS W-PLAN POL objective 60x/0.80	
M-1060	IOS W-PLAN F objective 4x/0.13	
M-1061	IOS W-PLAN F objective 10x/0.30	
M-1062	IOS W-PLAN F objective 20x/0.50	
M-1063	IOS W-PLAN F objective 40x/0.75	
M-1064	IOS W-PLAN F objective 100x/1.30 (oil)	
M-175	Rotating table for polarising set	
M-635	Heating stage, with digital temperature controller (only on newly purchased microscopes)	
M-181	Complete Phase Contrast Set with IOS W-PLAN obj. 10x, 20x, 40x, 100x and BF/DF/PH condenser	
M-185	Darkfield condenser for dry objectives	
M-620	0.35x focusable C-Mount adapter (biological microscopes)	
M-620.1	0.5x focusable C-Mount adapter (biological microscopes)	
M-620.2	0.65x focusable C-Mount adapter (biological microscopes)	
M-620.3	1x focusable C-Mount adapter (biological microscopes)	
M-173	Photo adapter for APS-C and Full Frame Reflex cameras	
M-699	Universal adapter for M-173	
M-1004.N	Centering telescope, 30mm diameter	
M-005	Micrometric slide, 26x76mm, with 2 X scales (1mm/100div. for biological / 10mm/100div. for stereo)	
M-636	Polarising set (filters only) for B-510 series	
M-1037	Gout analysis kit	
M-977	Green filter, 45 mm diameter	
M-979	Yellow filter, 45 mm diameter	
M-989	Frosted glass filter, 45 mm diameter	
M-690	Eyecups (pair)	
15104	Cleaning kit	
15008	Immersion oil, 10ml	
VP-510	IQ/OQ/PQ Manual for B-510 series	
DC-003	TNT dust cover, medium 600(l)x550(h) mm	